



REBOKE NINJA 40000, 33000, 24000 and 19000

The champions in efficiency for the champions in productivity!





REBOKE NINJA

With strong tradition in production of agricultural chaser bins, Stara releases its new line Rebokes Ninja. Developed for grain transport, the new Rebokes Ninja were created with base in three assumptions: design, competitiveness and robustness.

Rebokes Ninja have a modern, ergonomic and bold design. They are available in 4 models: Reboke Ninja 19000, Reboke Ninja 24000, Reboke Ninja 33000 and Reboke Ninja 40000.

The new Rebokes Ninja were developed to reach high performance at work, that is, with a 500 mm carbon steel unloading tube, with an unloading capacity of up to 10000 kg/min* in models Rebke Ninja 33000 and Reboke Ninja 40000, and up to 8500 kg/min* in models Reboke Ninja 24000 and Reboke Ninja 19000.

**Depending on the type of product, moisture and density.*



PATENT PENDING

CAPACITY OF 40 m³



Mouthpiece
The line Reboke Ninja has a steerable mouthpiece that enables better distribution of the load on the truck being unloaded.

500 mm
All models of Reboke Ninja have 500 mm unloading pipe for greater flexibility and speed at grain unload.

BETTER TURNING RADIUS
FACILITATES MANEUVER IN TILLAGE

Unloading pipe
The unloading pipe of Rebokes Ninja has high unloading capacity with only 2 helicoids and angular alignment between the 2 stages of the auger, providing better visualization of the grain unloading.

Reboke Ninja 19000

CAPACITY OF 19 m³



Reboke Ninja 24000

CAPACITY OF 24 m³



Reboke Ninja 33000

CAPACITY OF 33 m³





Technical Specifications

Model			
Reboke Ninja 19000	Reboke Ninja 24000	Reboke Ninja 33000	Reboke Ninja 40000
Load capacity			
19 m ³	24 m ³	33 m ³	40 m ³
Unloading pipe			
500 mm	500 mm	500 mm	500 mm
*Tank height			
3.540 mm	3.610 mm	3.820 mm	3.770 mm
**Tank height			
3.270 mm	3.340 mm	3.550 mm	3.500 mm
Tank length			
4.495 mm	5.110 mm	5.990 mm	6.845 mm
Tank width			
2.985 mm	3.190 mm	3.190 mm	3.190 mm
*** Unloading height			
4.335 mm	4.550 mm	4.655 mm	4.500 mm
Unloading activation			
Tractor PTO	Tractor PTO	Tractor PTO	Tractor PTO
Options of wheels for tires			
STANDARD WHEEL 30.5L-32	STANDARD WHEEL 23.1-26 x 23.1-26	STANDARD WHEEL 30.5L-32 x 30.5L-32	STANDARD WHEEL 850/50R30.5 x 850/50R30.5
OPTIONAL WHEEL 850/50R30.5	OPTIONAL WHEEL 650/65R30.5 x 650/65R30.5	OPTIONAL WHEEL 650/65R30.5 x 650/65R30.5	
Optional items			
Hydraulic brake	Hydraulic brake	Hydraulic brake	Hydraulic brake

*Approximate height for the higher side of the tank

**Approximate height for the lower side of the tank

***Approximate height with standard wheel

Note: All measurements are with standard wheel